KT-DPF | Multi-range cable grommets, black

in pyramid shape, for cable diameters 3-26 mm / IP54



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

Black KT-DPF grommets have an increased chemical resistance, e.g. against aggressive oils, coolants etc.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

It is recommended that additional strain relief be provided for the cables using a cable tie.

Cutting of KT-DPF grommets: Cable diameter less 20%.

Specifications

IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-HB
Operating temperature	-30 C° to 90 C°
Properties	higher chemical resistance

Advantages & benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

Product types & sizes

KT-DPF-A bk



Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

Height Mounting height Clamping range Clamping range 50 mm 33 mm 3 - 12 mm 1 x 3 - 12 mm

KT-DPF-B bk



Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41361 4251269307119 10 1 black 41,5 mm 42 mm Height Mounting height For cable type Clamping range Clamping range

59 mm 42 mm Round cable 4 - 18 mm 1 x 4 - 18 mm



Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41362 4251269307126 10 1 black 41,5 mm

42 mm

Height Mounting height For cable type Clamping range Clamping range 59 mm 42 mm Round cable 14 - 26 mm 1 x 14 - 26 mm

